


# SONOLIGHT AD-L ALSDL-L

[Download Wentyle](#)  
[Download AlnorCAM](#)  
[Buy via B2B](#)



## Dimensions



## Description

Flexible duct, noise and heat insulated, with additionally perforated ALUDUCT AD-L insert. Insulated with a 25mm thick mineral wool, covered with aluminium-polyester film casing.

**Packaging:** 10m sections, squeezed to 1200mm, packed into cardboard boxes.

**Flexibility rate (winding diameter):** Relative to a specific external diameter, i.e. approx. 0.75 x diameter in mm.

**Temperature range:** - 30°C to + 120°C

**Allowable negative pressure:** Allowable negative pressure: Depending on duct position. For straight sections, you can assume 1/3 of transmitted pressure per diameter.

**Noise insulation:** See the attached diagram.

The duct is also available without perforation. **IZOLIGHT AD-L ALIDL-L**

Fire classification - E.g. -1258.1/A/07/MŽ

### Example identification

Product code: **ALSDL-L - aaa**

type \_\_\_\_\_  
Ød₁ \_\_\_\_\_

Ød <sub>1</sub> rated [mm]	Ød ext [mm]	allowable pressure [Pa]	tolerance [mm]
80	82,0	2000	+ 1,5
100	102,0	2000	+ 1,5
125	127,0	2000	+ 1,5
140	140,0	2000	+ 1,5
150	152,0	2000	+ 1,5
160	160,0	2000	+ 2,0
180	180,0	2000	+ 2,0
200	203,0	2000	+ 2,0
225	229,0	2000	+ 2,0
250	254,0	2000	+ 3,0
280	280,0	2000	+ 3,0
300	305,0	2000	+ 3,0
315	315,0	2000	+ 3,0
355	355,0	2000	+ 3,0
400	406,0	2000	+ 3,0
450	457,0	2000	+ 3,0
500	508,0	2000	+ 3,0